



BIOCIDE

EPA Reg. No. 464-426-73749

Bond 1260

BROAD SPECTRUM MICROBIOCIDES

Application

Bond 1260 has been designed to provide broad spectrum control of bacterial growth in industrial recirculating cooling systems, once-through cooling systems, air-washing systems, enhanced oil recovery systems, and paper mills.

Advantages

- Compatible with standard cooling treatments
- Effective against sulfate reducing bacteria
- Effective at low dosages
- Liquid for ease of application
- Very little odor

Dosage

Badly fouled systems must be cleaned before treatment.

INITIAL DOSE: An initial dose of 0.6 – 1.2 ounces of Bond 1260 per 1000 gallons of system water will control bacterial growth. For control of fungi and algae, use an initial dose of 6.1 – 12.2 fluid ounces of Bond 1260 per 1000 gallons of system water.

SUBSEQUENT DOSE: When control is evident, add 0.12 – 1.2 fluid ounces of Bond 1260 per 1000 gallons of system water every four days or as needed to maintain control of bacteriological growth. For control of fungi and algae add a subsequent dosage of 3.1 – 12.2 fluid ounces of Bond 1260 per 1000 gallons of system water daily or as needed to maintain control.

Feeding

Bond 1260 should be fed as received to any point of rapid circulation.

Product Data

FORM:	Liquid
pH:	2.9
SPECIFIC GRAVITY:	1.2 – 1.3

Handling

Causes severe burns to eyes. Eye contact may cause loss of vision. May burn skin. May be harmful or fatal if swallowed. Do not get in eyes, on skin, or on clothing. In case of contact, flush eyes with plenty of water for 15 minutes and get medical attention. In case of skin contact, wash with soap and water. If swallowed, induce vomiting. Call a physician. Consult Material Safety Data Sheet for further safety information.

Packaging

55 Gallon Drum – 30 Gallon Drum – 5 Gallon Pail